

Gardner Denver


MODULAR DESICCANT DRYER | 3-177 CFM

XGML Series



X Series: NeXt-Generation Gardner Denver Air Treatment

XGML SERIES MODULAR DESICCANT DRYERS



Improve Air Quality Output, Reduce Operating Costs

Innovative modular air dryers by Gardner Denver make it easier and more affordable than ever to deliver high-quality compressed air for instrumentation, process equipment, or production lines—virtually wherever it is needed:

- High-efficiency filtration and desiccant bed adsorption provide clean, dry air
- Compact, fully integrated units install at point-of-use, so you pay for drying only the air required
- Conservative pressure drop lowers power costs
- Optional energy management system for larger units reduces purge air during partial loads

Enhance Productivity

Our dryers feature standard ISO Class 2 dewpoint performance, with optional ISO Class 1 to meet the most stringent requirements. This helps prevent corrosion and minimizes production disruptions or losses due to moisture or contamination. And easy on-site maintenance—less than 15 minutes after 12,000 hours of use—gets you back on line quickly.

Extend Performance Reliability

In addition to being efficient, these simple and easy-to-maintain modular dryers are also an excellent long-term investment:

- Extruded aluminum construction with Alocrom and epoxy painting prevents corrosion
- Compact, modular designs have few moving parts
- Proven, reliable electronic controls, with control panel indication for preventive maintenance, help ensure long-lasting performance
- Warranty coverage you can trust: 12 months from start up or 18 months from shipment



Promote Environmental Safety

Because noise levels (<75 dB) are so low, Gardner Denver modular dryers can be installed right in the work environment. In addition, the dryer's remote exhaust feature offers further enhanced noise suppression. These refrigerant-free units are also designed with NEMA 4/IP-66 enclosures and in accordance with ASME, PED, CSA, UL, and CRN standards.

SPECIFICATIONS: XGML SERIES | MODULAR AIR DRYERS

MODEL	CAPACITY		INLET/OUTLET CONNECTION NPT (IN)	MAX. PRESSURE		DIMENSIONS W × D × H		WEIGHT	
	SCFM	M ³ /HR		PSIG	BARG	INCHES	MM	LB	KG
XGML3	3	5	3/8"	203	14	9.4 × 8.3 × 16.7	238 × 212 × 423	24.2	11
XGML9	9	15	3/8"	203	14	9.4 × 8.3 × 32.4	238 × 212 × 823	39.7	18
XGML15	15	25	3/8"	203	14	9.4 × 8.3 × 42.2	238 × 212 × 1073	59.5	27
XGML24	24	40	3/4"	203	14	18.7 × 15.9 × 38.1	475 × 405 × 968	97	44
XGML32	32	55	3/4"	203	14	18.7 × 15.9 × 44	475 × 405 × 1118	110.2	50
XGML41	41	70	3/4"	203	14	18.7 × 15.9 × 51.9	475 × 405 × 1318	132.2	60
XGML59	59	100	1"	203	14	18.7 × 15.9 × 65.9	475 × 405 × 1673	160.9	73
XGML88	88	151	1"	203	14	18.7 × 15.9 × 73.7	475 × 405 × 1873	198.4	90
XGML118	118	200	1 1/2"	203	14	21.1 × 19.5 × 67.1	536 × 495 × 1705	390.1	177
XGML147	147	251	1 1/2"	203	14	21.1 × 19.5 × 75	536 × 495 × 1905	396.7	180
XGML177	177	300	1 1/2"	203	14	21.1 × 19.5 × 75	536 × 495 × 1905	414.4	188

XGML Benefits

- Minimize contaminants, corrosion, energy use
- Reduce costs by treating only the air you need
- Deliver quiet performance on the spot
- Sustain high efficiency with easy maintenance

The leader in every market we serve
by continuously improving all business processes
with a focus on innovation and velocity

**Gardner
Denver**[®]

Gardner Denver, Inc.

1800 Gardner Expressway
Quincy, IL 62305

www.gardnerdenver.com/gdproducts



©2022 Gardner Denver, Inc. Printed in U.S.A.
GA-XGML 3rd Ed. 1/22

 Please recycle after use.